

## Stainless Steel Cleanroom Doors

Product type	: Cleanroom door
Applicable Standards	: ISO 14644 - Class 5/6/7/8 : EU-GMP - Class A/B/C/D
Model Numbers	: SD / Single Door – UDD / Unequal Double Doors : EDD / Equal Double Doors
Window Type	: Double glazed window provided with safety glass (toughened or laminated) : available with round or square corners. : Black or white borders, windows are filled with inert gas and desiccants, : thicknesses 50/75/100 mm (flush with partition wall)
Window Frame Material	: Stainless Steel 304/316
Door Leaf Material	: Stainless Steel 304/316, thickness 1.0 mm
Infill Material	: Flame retardant paper honeycomb – Fire-proof aluminum honeycomb : Rockwool – Polyurethane foam
Door Thicknesses	: 50/75/100 mm
Door Sizes	: According requirements
Gasket Type	: EPDM or Silicone
Locks	: Standard KABA – 2000 series with stainless steel front plate : According requirements
Handle	: Standard KABA – 2000 series, stainless steel : According requirements
Door closer	: Standard KABA, surface mounted – built-in – automatic
Drop Doan Seal	: Lelonlock
Hinges	: GCR stainless steel 304/316

### Hardware Options

- Panic bar
- Kick plate
- 2/3/4/5 doors interlock system, including magnets, push buttons / no-touch buttons
- Doorstop
- Push / pull handle
- Exit device